

C.I.P.	Rimmed cartridges	TABLE II	
		DATE	84-06-09
		REV.	02-05-15

Calibres of rifled long centre fire weapons for rimmed cartridges.

The metric calibres are classed before the calibres originally designated in inches.

The classification is in growing and in alphabetical order according to the designation of the calibre.

Transducer method

Calibre	country of origin	Date	Rev.	M	PTmax	PK	PE	EE
5,6 x 35 R	DE	84-06-14	02-05-15	17,5	2700	3105	3375	855
5,6 x 50 R Mag.	DE	88-02-04	02-05-15	25	3400	3910	4250	1950
5,6 x 52 R	DE	84-06-14	02-05-15	25	3300	3795	4125	1830
5,6 x 57 R	DE	84-06-14	02-05-15	25	4400	5060	5500	2720
5,6 x 61 R SE v. H.	DE	84-06-14	02-05-15	25	3800	4370	4750	2945
6 x 50 R Scheiring	AT	87-09-29	02-05-15	25	4400	5060	5500	2100
6 x 52 R Bretschneider	DE	98-01-27	02-05-15	25	3300	3795	4125	2205
6 x 62 R Freres	DE	92-02-27	02-05-15	25	4300	4945	5375	3435
6 x 70 R	DE	00-06-28	02-05-15	25	2600	2990	3250	1785
6,5 x 50 R	DE	92-02-27	02-05-15	25	3650	4198	4563	2500
6,5 x 51 R (Arisaka)	JP	84-06-14	02-05-15	25	2950	3393	3688	2625
6,5 x 52 R	DE	84-06-14	02-05-15	25	2450	2818	3060	1810
6,5 x 57 R	DE	84-06-14	02-05-15	25	3300	3795	4125	3055
6,5 x 58 R	DE	84-06-14	02-05-15	25	2800	3220	3500	2300
6,5 x 65 R RWS	DE	90-04-05	02-05-15	25	3800	4370	4750	3675
6,5 x 68 R	DE	84-06-14	02-05-15	25	3900	4485	4875	3810
6,5 x 70 R	DE/AT	86-04-11	02-05-15	25	2800	3220	3500	1730
7 x 50 R	DE	92-02-27	02-05-15	25	3650	4198	4560	2940
7 x 57 R	DE	84-06-14	02-05-15	25	3400	3910	4250	3390
7 mm Mag. Fl. H. & H.	GB	84-06-14	02-05-15	25	3300	3795	4125	3150
7 x 65 R	DE	84-06-14	02-05-15	25	3800	4370	4750	4170
7 x 72 R	DE	84-06-14	02-05-15	25	2800	3220	3500	2890
7 x 75 R SE.v. H.	DE	84-06-14	02-05-15	25	4150	4773	5190	4830
7,62 x 53 R	FI	84-06-14	02-05-15	25	3900	4485	4875	3960
7,62 x 54 R	SU	84-06-14	02-05-15	25	3900	4485	4875	3960
8 x 50 R	AT	89-10-06	02-05-15	25	3550	4083	4440	3000
8 x 56 RM 30	DE	84-06-14	02-05-15	25	3400	3910	4250	2995
8 x 56 RM 30S	AT	88-01-30	02-05-15	25	3550	4083	4440	3933
8 x 56 RM Port. Krop.	PT	84-06-14	02-05-15	25	3400	3910	4250	2520
8 x 57 R 360	DE	84-06-14	02-05-15	25	2450	2818	3060	2170
8 x 57 IR	DE	84-06-14	02-05-15	25	3200	3680	4000	3315
8 x 57 IRS	DE	84-06-14	02-05-15	25	3300	3795	4125	3955



PTmax = maximum average pressure (bar)

PK = 1,15 Pmax = maximum statistical individual pressure (bar)

PE = 1,25 Pmax = mean proof pressure (bar)

M = location of the pressure take (mm)

EE = proof kinetic energy (Joule)

Notice: For conformal or tangential transducers the location (M) is that defined by the manufacturer.

Mag. = Magnum

Fl.NE = Flanged Nitro Express

Sld. = Solid

SL = Self Loading

H.&H. = Holland and Holland

sh = short

lg = long

B.P. = Black Powder

R = Rand = à bourrelet

SE v.H. = Super Express vom Hofe

Win. = Winchester

Mag.Fl.H&H = Magnum Flanged Holland & Holland

C.I.P.	Rimmed cartridges	TABLE	II
		DATE	84-06-09
		REV.	02-05-15

Calibres of rifled long centre fire weapons for rimmed cartridges.

The metric calibres are classed before the calibres originally designated in inches.

The classification is in growing and in alphabetical order according to the designation of the calibre.

Transducer method

(Suite)

Calibre	country of origin	Date	Rev.	M	PTmax	PK	PE	EE
8 x 58 R	DE	84-06-14	02-05-15	25	2200	2530	2750	2270
8 x 60 R	DE	84-06-14	02-05-15	25	3400	3910	4250	3780
8 x 60 RS	DE	84-06-14	02-05-15	25	3400	3910	4250	4120
8 x 65 R	DE	84-06-14	02-05-15	25	3900	4485	4875	4410
8 x 65 RS	DE	84-06-14	02-05-15	25	4050	4658	5060	4620
8 x 72 R	DE	84-06-14	02-05-15	25	2800	3220	3500	2565
8 x 75 RS	DE	84-06-14	02-05-15	25	3800	4370	4750	4790
8 mm - 348 Win	FR	99-03-16	02-05-15	25	3000	3450	3750	2600
8,15 x 46 R	DE	84-06-14	02-05-15	25	1650	1898	2060	1785
8,2 x 53 R	FI	95-03-09	02-05-15	25	3400	3910	4250	4040
8,5 x 63 R	DE	92-02-27	02-05-15	25	3800	4370	4750	5145
9 x 53 R	RU	99-03-23	02-05-15	25	3400	3910	4250	3800
9 x 57 R	DE	84-06-14	02-05-15	25	2800	3220	3500	3260
9,3 x 53 R Finnish	FI	95-03-09	02-05-15	25	3400	3910	4250	4300
9,3 x 72 R	DE	84-06-14	02-05-15	25	2000	2300	2500	2325
9,3 x 74 R	DE	84-06-14	02-05-15	25	3400	3910	4250	5045
10,3 x 60 R	CH	84-06-14	02-05-15	25	2700	3105	3375	4620
11,15 x 60 R	DE	84-06-14	02-05-15	25	2800	3220	3500	2730
218 Bee	US	84-06-14	02-05-15	17,5	3200	3680	4000	1115
219 Zipper	US	84-06-14	02-05-15	25	2850	3278	3560	1935
22 Hornet	US	84-06-14	02-05-15	17,5	3000	3450	3750	1055
22 Savage	US	84-06-14	02-05-15	25	3300	3795	4125	1990
225 Win.	US	84-06-14	02-05-15	25	3900	4485	4875	2195
240 Fl. N.E.	GB	84-06-14	02-05-15	25	3200	3680	4000	2660
25-20 Win.	US	84-06-14	02-05-15	17,5	2700	3105	3375	1090
25-35 Win.	US	84-06-14	02-05-15	25	3050	3508	3810	1750
256 Win. Mag.	US	84-06-14	02-05-15	17,5	3500	4025	4375	1365
7-30 Waters	US	91-02-19	02-05-15	25	3400	3910	4250	2760
280 Fl. N.E.	GB	84-06-14	02-05-15	25	2950	3393	3690	3550

(suite)

PTmax = maximum average pressure (bar)

PK = 1,15 Pmax = maximum statistical individual pressure (bar)

PE = 1,25 Pmax = mean proof pressure (bar)

M = location of the pressure take (mm)

EE = proof kinetic energy (Joule)

Notice: For conformal or tangential transducers the location (M) is that defined by the manufacturer.

Mag. = Magnum

Fl.NE = Flanged Nitro Express

Sld. = Solid

SL = Self Loading

H.&H. = Holland and Holland

sh = short

lg = long

B.P. = Black Powder

R = Rand = à bourrelet

SE v.H. = Super Express vom Hofe

Win. = Winchester

Mag.Fl.H&H = Magnum Flanged Holland & Holland



C.I.P.	Rimmed cartridges	TABLE	II
		DATE	84-06-09
		REV.	02-05-15

Calibres of rifled long centre fire weapons for rimmed cartridges.

The metric calibres are classed before the calibres originally designated in inches.

The classification is in growing and in alphabetical order according to the designation of the calibre.

Transducer method

(Suite)

Calibre	Country of origin	Date	Rev.	M	PTmax	PK	PE	EE
297/230 Morris lg	GB	84-06-14	00-06-07					
297/230 Morris sh	GB	84-06-14	00-06-07					
297/250 Rook Rifle	GB	84-06-14	00-06-07					
30 R Blaser	DE	91-02-19	02-05-15	25	4050	4658	5060	4500
30 Fl.N.E. Purdey	GB	84-06-14	02-05-15	25	3200	3680	4000	3455
30 Super Fl. H.& H.	GB	84-06-14	02-05-15	25	3200	3680	4000	3520
30-30 Win.	US	84-06-14	02-05-15	25	3200	3680	4000	2445
30-40 Krag	US	84-06-14	02-05-15	25	3250	3738	4060	3750
300/295 Rook Rifle	GB	84-06-14	02-05-15	17,5	1200	1380	1500	375
300 Sherwood	GB	84-06-14	02-05-15	25	1400	1610	1750	930
303 British	GB	84-06-14	02-05-15	25	3650	4198	4560	2910
303 Savage	US	84-06-14	02-05-15	25	2700	3105	3375	2455
303 Sporting	FR	00-11-13	02-05-15	25	3300	3795	4125	2800
307 Win.	US	84-06-14	02-05-15	25	4150	4773	5190	2825
310 Cadet Rifle	GB	84-06-14	02-05-15	17,5	1100	1265	1375	680
32 Win. SL	US	84-06-14	02-05-15	17,5	1550	1783	1940	1080
32 Win. Spec.	US	84-06-14	02-05-15	25	3050	3508	3810	2370
32-20 Win.	US	84-06-14	02-05-15	17,5	2100	2415	2625	1560
32-40 Win.	US	84-06-14	02-05-15	25	2350	2703	2940	1105
33 Win.	US	84-06-14	02-05-15	25	3050	3508	3810	4015
348 Win.	US	84-06-14	02-05-15	25	3200	3680	4000	3640
35 Win.	US	84-06-14	02-05-15	25	3050	3508	3810	4145
35 Win. SL	US	84-06-14	02-05-15	17,5	2400	2760	3000	1150
350 No. 2 Rigby	GB	84-06-14	02-05-15	25	3300	3795	4125	4900
351 Win. SL	US	84-06-14	02-05-15	17,5	3650	4198	4560	1330
356 Win.	US	84-06-14	02-05-15	25	4150	4773	5190	3705
360 N.E. 2"1/4	GB	84-06-14	02-05-15	25	2450	2818	3060	2285
369 N.E. Purdey	GB	84-06-14	02-05-15	25	3050	3508	3810	4130
375 Fl. N.E. 2"1/2	GB	84-06-14	02-05-15	25	2200	2530	2750	3220
375 Fl. Mag. N.E.	GB	84-06-14	02-05-15	25	3250	3738	4060	5925
375 Win.	US	84-06-14	02-05-15	25	4400	5060	5500	2930

(suite)

PTmax = maximum average pressure (bar)

PK = 1,15 Pmax = maximum statistical individual pressure (bar)

PE = 1,25 Pmax = mean proof pressure (bar)

M = location of the pressure take (mm)

EE = proof kinetic energy (Joule)

Notice: For conformal or tangential transducers the location (M) is that defined by the manufacturer.

Mag. = Magnum

Fl.NE = Flanged Nitro Express

Slid. = Solid

SL = Self Loading

H.&H. = Holland and Holland

sh = short

lg = long

B.P. = Black Powder

R = Rand = à bourrelet

SE v.H. = Super Express vom Hofe

Win. = Winchester

Mag.Fl.H&H = Magnum Flanged Holland & Holland



C.I.P.	Rimmed cartridges	TABLE	II
		DATE	84-06-09
		REV.	02-05-15

Calibres of rifled long centre fire weapons for rimmed cartridges.

The metric calibres are classed before the calibres originally designated in inches.

The classification is in growing and in alphabetical order according to the designation of the calibre.

Transducer method

(Suite)

Calibre	Country of origin	Date	Rev.	M	PTmax	PK	PE	EE
38-40 Win.	US	84-06-14	02-05-15	17,5	1150	1323	1440	1945
38-55 Win.	US	84-06-14	02-05-15	25	2400	2760	3000	1580
380 Long Rifle	GB	84-06-14	02-05-15	17,5	950	1093	1190	412
40-82 Win.	US	84-06-14	02-05-15	25	1650	1898	2060	1590
400 N.E. B.P. 3" Purdey	GB	84-06-14	00-06-07					
400/350 N.E.	GB	84-06-14	02-05-15	25	2800	3220	3500	4292
401 Win. SL	US	84-06-14	02-05-15	25	2450	2818	3060	2655
405 Win.	US	84-06-14	02-05-15	25	2450	2818	3060	4490
408 Win.	US	84-06-14	02-05-15	25	4100	4715	5125	4190
44-40 Win.	US	84-06-14	02-05-15	17,5	1100	1265	1375	890
444 Marlin	US	84-06-14	02-05-15	25	3550	4083	4440	3287
45-70 Elko Mag.	BE	92-07-28	02-05-15	25	2950	3393	3690	6400
45-70 Govt.	US	84-06-14	02-05-15	25	2200	2530	2750	3414
450 N.E. 3"1/4	GB	84-06-14	02-05-15	25	3050	3508	3810	3070
450 N° 2 N.E. 3"1/2 Eley	GB	98-01-27	02-05-15	25	2800	3220	3500	7140
450/400 N.E. 3"	GB	84-06-14	02-05-15	25	2800	3220	3500	5310
450/400 Mag.N.E. 3"1/4	GB	84-06-14	02-05-15	25	2950	3393	3690	6993
470 N.E.	GB	84-06-14	02-05-15	25	2700	3105	3375	6957
475 N° 2 N.E. 3"1/2	GB	84-06-14	02-05-15	25	2750	3163	3440	6957
475 N° 2 N.E. 3"1/2 Jeffery	GB	98-01-27	02-05-15	25	2750	3163	3575	6957
500 N.E. 3"	GB	84-06-14	02-05-15	25	2800	3220	3500	8400
500/416 N.E. 3"1/4	GB	96-12-20	02-05-15	25	3150	3623	3940	6720
500/465 N.E.	GB	84-06-14	02-05-15	25	2450	2818	3060	6372
577/450 Sld. Mart.H.	GB	84-06-14	02-05-15	25	1750	2013	2190	2532
577 N.E. 3"	GB	84-06-14	02-05-15	25	2450	2818	3060	9975
577 Sld. Snider	GB	84-06-14	02-05-15	25	1500	1725	1875	2290
600 N.E.	GB	84-06-14	02-05-15	25	2450	2818	3060	10323
700 H.& H. Nitro Exp.	GB	92-04-06	02-05-15	25	2750	3163	3440	14325
4 Bore Rifle	US	93-09-27	02-05-15	25	2500	2875	3125	10500

PTmax = maximum average pressure (bar)

PK = 1,15 Pmax = maximum statistical individual pressure (bar)

PE = 1,25 Pmax = mean proof pressure (bar)

M = location of the pressure take (mm)

EE = proof kinetic energy (Joule)

Notice: For conformal or tangential transducers the location (M) is that defined by the manufacturer.

Mag. = Magnum

Fl.NE = Flanged Nitro Express

Sld. = Solid

SL = Self Loading

H.&H. = Holland and Holland

sh = short

lg = long

B.P. = Black Powder

R = Rand = à bourrelet

SE v.H. = Super Express vom Hofe

Win. = Winchester

Mag.Fl.H&H = Magnum Flanged Holland & Holland

