



Handgun Loading Data - 25 ACP

WARNING: Reduce listed load by 10% for a start charge

25 ACP

Gun: RAVEN

Barrel length: 2"

Primer: WIN SP*

Case: HDY

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
50	0.900"	No.2	1.6	717

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Accurate

Handgun Loading Data - 32 & 32/20

WARNING: Reduce listed load by 10% for a start charge

32 S&W LONG

Gun: DOUGLAS
Barrel: length 6"
Primer: FED 100*
Case: REM

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
90 (HB)	0.930"	No.2	2.0	786
90	1.190"	No.2	2.5	886

32/20 WINCHESTER

Gun: RUGER BLACKHAWK
Barrel length: 6"
Primer: CCI 400*
Case: REM

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
100 (L)	1.585"	No.5	4.8	865
SWC	1.585"	No.7	6.1	924
90	1.565"	No.5	5.0	906
90	1.565"	No.7	6.1	937
100	1.565"	No.5	4.7	844
100	1.565"	No.7	5.8	887

32 H&R MAGNUM

Gun: DOUGLAS
Barrel length: 10"
Primer: CCI 500*
Case: FED

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
100 (L)	1.310"	No.2	3.6	1160

SWC	1.310"	No.5	4.7	1261
85	1.325"	No.2	4.0	1269
85	1.325"	No.5	5.3	1336
100	1.335"	No.2	3.7	1146
100	1.335"	No.5	5.0	1224

32/20 CONTENDER ONLY

Gun: DOUGLAS

Barrel length: 14"

Primer: CCI 400*

Case: REM

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
100 (L)	1.585"	No.5	6.0	1342
SWC	1.585"	No.7	7.0	1325
90	1.565"	No.5	6.2	1375
90	1.565"	No.7	7.8	1461
100	1.585"	No.5	6.0	1330
100	1.585"	No.7	7.4	1365

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 380 Auto

WARNING: Reduce listed load by 10% for a start charge

380 AUTO

Gun: OBERMEYER

Barrel length: 3"

Primer CCI: 500*

Case: FED

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
100 (L)	0.950"	No.2	3.6	943
100 (L)	0.950"	No.5	4.5	922
90	0.960"	No.2	3.7	930
90	0.960"	No.5	4.8	920
95	0.945"	No.2	3.7	934
95	0.945"	No.5	4.8	891
100	0.975"	No.2	3.4	793
100	0.975"	No.5	4.9	895

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 9 MM

WARNING: Reduce listed load by 10% for a start charge

9mm LUGER

Gun: OBERMEYER

Barrel length: 4"

Primer: WIN SP*

Case: FED

Maximum Loads

Bullet	OAL	Powder.	Grains	Vel.
115 (L)	1.100"	No.2	4.9	1146
115 (L)	1.100"	No.5	6.3	1182
115 (L)	1.100"	No.7	8.7	1225
125 (L)	1.100"	No.2	4.5	1063
125 (L)	1.100"	No.5	6.2	1133
125 (L)	1.100"	No.7	8.3	1156
145 (L)	1.140"	No.2	3.7	893
145 (L)	1.140"	No.5	5.1	984
145 (L)	1.140"	No.7	7.2	1052
115	1.095"	No.2	4.4	1092
115	1.095"	No.5	7.0	1192
115	1.095"	No.7	8.8	1196
124	1.095"	No.2	4.1	1057
124	1.095"	No.5	6.4	1200
124	1.095"	No.7	8.0	1166
147	1.095"	No.2	4.0	888

147	1.095"	No.5	5.3	991
147	1.095"	No.7	7.2	1047

Note: Some high performance handguns (such as the Glock and Sig/Sauer) may not cycle properly with the faster powders.

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 38

WARNING: Reduce listed load by 10% for a start charge

38 SPECIAL

Gun: S&W MODEL 14

Barrel length: 8-3/8

Primer: CCI 500*

Case: HDY

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
148 DE	1.252"	N100	2.7	863
148 DE	1.252"	S1000	2.7	830
148 DE	1.252"	No.2	3.5	850
148 DE	1.252"	No.5	5.0	912
148 HB	1.152"	N100	2.8	882
148 HB	1.152"	S1000	2.8	837
148 HB	1.152"	No.2	2.9	720
148 HB	1.152"	No.5	4.0	807
158 (L)	1.481"	N100	3.3	898
158 (L)	1.481"	S1000	3.4	857
158 (L)	1.481"	No.2	4.0	868
158 (L)	1.481"	No.5	5.9	940
110	1.435"	N100	4.4	1153
110	1.435"	S1000	4.4	1094
110	1.435"	No.2	5.6	1083
110	1.435"	No.5	7.3	1090
125	1.445"	N100	4.1	1031
125	1.445"	S1000	4.1	1010

38 SUPER AUTO

Gun: WILSON

Barrel length: 5"

Primer: CCI 500*

Case: PMC

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
115 (L)	1.285"	No.2	4.8	1133
115 (L)	1.285"	No.5	7.6	1267
115 (L)	1.285"	No.7	9.8	1320
115 (L)	1.285"	No.9	12.5	1374
130 (L)	1.220"	No.2	4.4	1102
130 (L)	1.220"	No.5	7.0	1185
130 (L)	1.220"	No.7	9.0	1244
130 (L)	1.220"	No.9	11.5	1257
145 (L)	1.250"	No.2	4.8	1078
145 (L)	1.250"	No.5	6.8	1168
145 (L)	1.250"	No.7	8.5	1165
145 (L)	1.250"	No.9	10.5	1207
160 (L)	1.250"	No.2	4.5	1025
160 (L)	1.250"	No.5	6.0	1048
160 (L)	1.250"	No.7	8.0	1115
160 (L)	1.250"	No.9	9.5	1116
115	1.240"	No.2	5.7	1200
115	1.240"	No.5	8.3	1321

125	1.445"	No.2	5.3	990
125	1.445"	No.5	6.8	860
140	1.445"	N100	3.9	933
140	1.445"	S1000	3.9	889
140	1.445"	No.2	4.7	888
140	1.445"	No.5	6.4	860
158	1.445"	N100	3.2	786
158	1.445"	S1000	3.4	798
158	1.445"	No.2	4.0	756
158	1.445"	No.5	5.8	841

115	1.240"	No.7	10.3	1340
115	1.240"	No.9	13.0	1395
124	1.245"	No.2	5.4	1163
124	1.245"	No.5	7.6	1230
124	1.245"	No.7	9.6	1263
124	1.245"	No.9	12.5	1346
130	1.250"	No.2	5.2	1116
130	1.250"	No.5	7.3	1201
130	1.250"	No.7	9.2	1209
130	1.250"	No.9	11.9	1305
135	1.250"	No.2	5.2	1140
135	1.250"	No.5	7.0	1140
135	1.250"	No.7	9.0	1190
135	1.250"	No.9	10.7	1199
150	1.250"	No.2	4.8	1038
150	1.250"	No.5	6.5	1075
150	1.250"	No.7	8.5	1148
150	1.250"	No.9	9.7	1111
158/160	1.250"	No.2	4.3	970
158/160	1.250"	No.5	6.2	1026
158/160	1.250"	No.7	8.0	1064
158/160	1.250"	No.9	9.7	1121

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 357

WARNING: Reduce listed load by 10% for a start charge

357 MAGNUM

Gun: S&W 686

Barrel length: 6"

Primer: CCI 500*

Case: HDY

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
158 (L)	1.580"	No.2	5.8	1074
158 (L)	1.580"	No.5	8.2	1239
158 (L)	1.580"	No.7	10.5	1239
158 (L)	1.580"	No.9	12.2	1280
110	1.575"	No.2	8.8	1324
110	1.575"	No.5	10.8	1340
110	1.575"	No.7	13.0	1424
110	1.575"	No.9	NR	
125	1.570"	No.2	8.2	1312
125	1.570"	No.5	10.1	1322
125	1.570"	No.7	12.0	1236
125	1.570"	No.9	NR	
140	1.575"	No.2	7.8	1199
140	1.575"	No.5	9.7	1205
140	1.575"	No.7	11.6	1215
140	1.575"	No.9	14.4	1349

357 SIG

Gun: HS PRECISION

Barrel length: 4"

Primer: FED 100*

Case: FED

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
115 (L)	1.140"	No.2	6.2	1249
115 (L)	1.140"	No.5	9.0	1319
115 (L)	1.140"	No.7	11.0	1344
115 (L)	1.140"	No.9	13.5	1430
122 (L)	1.140"	No.2	5.8	1217
122 (L)	1.140"	No.5	8.8	1300
122 (L)	1.140"	No.7	10.7	1321
122 (L)	1.140"	No.9	13.0	1383
147 (L)	1.140"	No.2	4.7	1049
147 (L)	1.140"	No.5	7.5	1170
147 (L)	1.140"	No.7	9.6	1218
147 (L)	1.140"	No.9	10.5	1170
SPR 88	1.130"	No.2	7.9	1545
SPR 88	1.130"	No.5	11.1	1616
SPR 88	1.130"	No.7	13.1	1601
SPR 88	1.130"	No.9	15.0	1545

158	1.580"	No.2	6.9	1088
158	1.580"	No.5	8.6	1080
158	1.580"	No.7	10.5	1139
158	1.580"	No.9	13.0	1261
180	1.575"	No.2	NR	
180	1.575"	No.5	8.0	1040
180	1.575"	No.7	9.4	1023
180	1.575"	No.9	11.7	1140

SRA 95	1.135"	No.2	7.6	1467
SRA 95	1.135"	No.5	11.0	1572
SRA 95	1.135"	No.7	13.0	1562
SRA 95	1.135"	No.9	15.0	1530
HDY 100	1.140"	No.2	7.3	1414
HDY 100	1.140"	No.5	10.5	1496
HDY 100	1.140"	No.7	12.2	1490
HDY 100	1.140"	No.9	14.5	1516
HDY 115	1.140"	No.2	6.4	1276
HDY 115	1.140"	No.5	9.4	1354
HDY 115	1.140"	No.7	11.3	1385
HDY 115	1.140"	No.9	13.5	1434
HDY 124	1.140"	No.2	6.0	1212
HDY 124	1.140"	No.5	9.2	1325
HDY 124	1.140"	No.7	11.0	1320
HDY 124	1.140"	No.9	13.0	1387
SRA 130	1.135"	No.2	6.0	1179
SRA 130	1.135"	No.5	8.8	1253
SRA 130	1.135"	No.7	10.4	1278
SRA 130	1.135"	No.9	12.0	1285
HDY 147	1.140"	No.2	5.3	1061
HDY 147	1.140"	No.5	7.9	1159
HDY 147	1.140"	No.7	9.2	1160
HDY 147	1.140"	No.9	10.5	1158

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 10 MM

WARNING: Reduce listed load by 10% for a start charge

10mm AUTO

Gun: HS PRECISION

Barrel length: 5"

Primer: CCI 300

Case: HDY

Maximum Loads

Bullet	OAL	Powder	Grains	Vel
145 (L)	1.250"	No.2	7.5	1293
145 (L)	1.250"	No.5	9.7	1352
145 (L)	1.250"	No.7	12.0	1367
145 (L)	1.250"	No.9	15.0	1422
175 (L)	1.245"	No.2	6.7	1167
175 (L)	1.245"	No.5	8.3	1166
175 (L)	1.245"	No.7	10.4	1199
175 (L)	1.245"	No.9	13.6	1285
205 (L)	1.250"	No.2	5.2	979
205 (L)	1.250"	No.5	7.0	1063
205 (L)	1.250"	No.7	9.3	1091
205 (L)	1.250"	No.9	11.8	1157
135	1.250"	No.2	9.1	1444
135	1.250"	No.5	11.4	1503
135	1.250"	No.7	13.6	1476
135	1.250"	No.9	17.5	1507

155	1.250"	No.2	8.0	1296
155	1.250"	No.5	10.0	1334
155	1.250"	No.7	12.7	1379
155	1.250"	No.9	15.9	1414
170	1.250"	No.2	7.7	1220
170	1.250"	No.5	9.7	1275
170	1.250"	No.7	12.0	1305
170	1.250"	No.9	15.0	1341
HDY 180	1.250"	No.2	6.8	1120
HDY 180	1.250"	No.5	8.7	1197
HDY 180	1.250"	No.7	10.7	1183
HDY 180	1.250"	No.9	13.5	1242
190	1.250"	No.2	7.2	1126
190	1.250"	No.5	9.1	1186
190	1.250"	No.7	11.2	1198
190	1.250"	No.9	14.2	1267
HDY 200	1.250"	No.2	6.3	1041
HDY 200	1.250"	No.5	7.8	1066
HDY 200	1.250"	No.7	9.8	1091
HDY 200	1.250"	No.9	12.5	1170

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 40 S&W

WARNING: Reduce listed load by 10% for a start charge

40 S&W

Gun: HS PRECISION

Barrel length: 4"

Primer: CCI 500*

Case: HDY

[\(WARNING: See below\)](#)

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
155 (L)	1.130"	No.2	6.3	1116
155 (L)	1.130"	No.5	7.5	1158
155 (L)	1.130"	No.7	9.7	1146
155 (L)	1.130"	No.9	12.0	1142
175 (L)	1.115"	No.2	5.3	975
175 (L)	1.115"	No.5	6.1	986
175 (L)	1.115"	No.7	8.4	1014
175 (L)	1.115"	No.9	10.2	998
205 (L)	1.110"	No.2	4.3	838
205 (L)	1.110"	No.5	5.0	836
205 (L)	1.110"	No.7	6.6	845
205 (L)	1.110"	No.9	8.7	880
135	1.125"	No.2	7.6	1247
135	1.125"	No.5	9.3	1266
135	1.125"	No.7	11.2	1237

135	1.125"	No.9	NR	
150	1.120"	No.2	7.0	1155
150	1.120"	No.5	8.3	1170
150	1.120"	No.7	10.2	1136
150	1.120"	No.9	NR	
HDY 180	1.135"	No.2	5.6	967
HDY 180	1.135"	No.5	6.6	965
HDY 180	1.135"	No.7	8.5	978
HDY 180	1.135"	No.9	11.0	1019
HDY 200	1.130"	No.2	4.7	815
HDY 200	1.130"	No.5	5.5	828
HDY 200	1.130"	No.7	7.4	850
HDY 200	1.130"	No.9	9.2	863

WARNING!!!

In recent years it has become very apparent that there exists a situation regarding some pistols chambered for the 40 S&W cartridge. Some of the pistols currently available to shooters may not provide complete support to the case when a cartridge is chambered.

The Sporting Arms and Ammunition Manufacturers Institute (SAAMI) has established a maximum average pressure for the 40 S&W of 35,000 psi. The loading data published by **Accurate Arms** was developed in our ballistic laboratory in accordance with SAAMI test methods and equipment and does not exceed this figure. This information is safe for use in firearms which provide complete support of the case. Failure to fully support the case with cartridges of such intensity may result in bulged cases, ruptured cases, separated case heads or other consequences which may result in damage to the firearm and/or injury or death to the shooter and/or bystanders. This can happen no matter whose propellant is used.

If you own a firearm chambered for the 40 S&W, we recommend you contact the manufacturer to determine if the case is fully supported, or have a competent gunsmith examine the firearm and determine the amount of support provided the case. If your firearm does not provide complete support for the case, **DO NOT USE Accurate Arms Company** data or products to reload your 40 S&W ammunition.

This is the first time **Accurate Arms Company** has felt it necessary to place such a restriction on the use of our products, but the continued safety and welfare of the shooting public compels us to do so.



Handgun Loading Data - 41 Mag.

WARNING: Reduce listed load by 10% for a start charge

41 REMINGTON MAGNUM

Gun: WILSON

Barrel length: 9-1/2"

Primer: CCI 300

Case: WIN

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
210 (L)	1.675"	No.2	9.2	1315
210 (L)	1.675"	No.5	12.5	1436
210 (L)	1.675"	No.7	14.5	1442
210 (L)	1.675"	No.9	18.0	1582
170	1.565"	No.2	10.0	1451
170	1.565"	No.5	12.0	1493
170	1.565"	No.7	15.5	1555
170	1.565"	No.9	19.7	1705
210	1.570"	No.2	9.5	1245
210	1.570"	No.5	11.5	1322
210	1.570"	No.7	14.2	1379
210	1.570"	No.9	18.0	1521

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 44

WARNING: Reduce listed load by 10% for a start charge

44 SPECIAL

Gun: DOUGLAS
Barrel length: 7-1/2"
Primer: CCI 300
Case: WIN

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
245 (L)	1.600"	N100	3.8	752
245 (L)	1.600"	S1000	4.5	791
245 (L)	1.600"	No.2	4.7	819
245 (L)	1.600"	No.5	6.8	860
240	1.485"	N100	3.8	583
240	1.485"	S1000	4.0	587
240	1.485"	No.2	4.5	604
240	1.485"	No.5	6.5	730

44 REMINGTON MAGNUM

Gun: RUGER REDHAWK
Barrel length: 7-1/2"
Primer: CCI 300
Case: WIN

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
240 (L)	1.560"	No.2	10.0	1280
240 (L)	1.560"	No.5	14.0	1400
240 (L)	1.560"	No.7	17.5	1458
240 (L)	1.560"	No.9	21.7	1550
300 (L)	1.720"	No.2	9.5	1138
300 (L)	1.720"	No.5	11.6	1140
300 (L)	1.720"	No.7	15.0	1245
300 (L)	1.720"	No.9	18.5	1320
180	1.560"	No.2	11.1	1444
180	1.560"	No.5	16.4	1615
180	1.560"	No.7	20.5	1707
180	1.560"	No.9	NR	
200	1.595"	No.2	11.0	1342
200	1.595"	No.5	15.8	1532
200	1.595"	No.7	18.7	1538
200	1.595"	No.9	25.0	1676

240	1.560"	No.2	10.0	1250
240	1.560"	No.5	14.4	1383
240	1.560"	No.7	17.3	1415
240	1.560"	No.9	21.3	1500
HDY 300	1.595"	No.2	9.8	1108
HDY 300	1.595"	No.5	13.0	1220
HDY 300	1.595"	No.7	14.5	1190
HDY 300	1.595"	No.9	17.7	1274

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 445 Super

WARNING: Reduce listed load by 10% for a start charge

445 SUPER MAG

Gun: DOUGLAS

Barrel length: 10"

Primer: FED 155

Case: Starline

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
300 (L)	2.055"	1680	32.0	1614
180	1.950"	1680	42.0	1994
200	1.920"	1680	40.0	1921
240	1.925"	1680	37.5	1806
HDY 300	2.060"	1680	31.5	1595

No. 9 not acceptable for use in this cartridge.

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 45

WARNING: Reduce listed load by 10% for a start charge

45 ACP

Gun: 1911A1

Barrel length: 5"

Primer: REM 2-1/2

Case: REM

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
155 (L)	1.240"	N100	5.5	1087
155 (L)	1.240"	S1000	6.5	1170
155 (L)	1.240"	No.2	7.5	1204
155 (L)	1.240"	No.5	10.0	1189
170 (L)	1.130"	N100	5.6	1082
170 (L)	1.130"	S1000	5.9	1059
170 (L)	1.130"	No.2	6.5	1079
170 (L)	1.130"	No.5	9.0	1074
200 (L)	1.190"	N100	4.9	938
200 (L)	1.190"	S1000	5.3	952
200 (L)	1.190"	No.2	5.8	939
200 (L)	1.190"	No.5	8.7	1025
230 (L)	1.230"	N100	4.5	834
230 (L)	1.230"	S1000	5.1	898
230 (L)	1.230"	No.2	5.6	870
230 (L)	1.230"	No.5	8.5	968
185	1.210"	N100	5.3	957
185	1.210"	S1000	5.8	993

45 COLT

Gun: DOUGLAS

Barrel length: 7-1/2"

Primer: CCI 300

Case: WIN

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
225 (L)	1.620"	N100	5.9	897
225 (L)	1.620"	S1000	6.5	909
225 (L)	1.620"	No.2	6.1	873
225 (L)	1.620"	No.5	12.1	1033
240 (L)	1.570"	N100	5.7	898
240 (L)	1.570"	S1000	6.3	851
240 (L)	1.570"	No.2	6.0	845
240 (L)	1.570"	No.5	11.3	998
255 (L)	1.600"	N100	5.5	868
255 (L)	1.600"	S1000	5.8	807
255 (L)	1.600"	No.2	5.9	813
255 (L)	1.600"	No.5	10.4	961
185	1.575"	N100	6.8	993
185	1.575"	S1000	7.6	1027
185	1.575"	No.5	12.0	1075
200	1.595"	N100	6.4	954
200	1.595"	S1000	7.0	932
200	1.595"	No.5	11.5	1032

185	1.210"	No.2	7.5	1077	230	1.595"	N100	5.7	843
185	1.210"	No.5	10.2	1102	230	1.595"	S1000	6.3	800
200	1.225"	N100	4.8	873	230	1.595"	No.5	11.0	969
200	1.225"	S1000	5.8	914	240	1.590"	N100	5.6	838
200	1.225"	No.2	6.5	963	240	1.590"	S1000	6.0	776
200	1.225"	No.5	9.7	1050	240	1.590"	No.5	10.5	970
230	1.250"	N100	4.5	825	250	1.570"	N100	5.5	757
230	1.250"	S1000	5.5	848	250	1.570"	S1000	5.8	750
230	1.250"	No.2	6.1	874	250	1.570"	No.5	11.0	800
230	1.250"	No.5	8.7	927	260	1.600"	N100	5.3	729
					260	1.600"	S1000	5.8	695
					260	1.600"	No.5	10.5	762

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 454 Casull

WARNING: Reduce listed load by 10% for a start charge

454 CASULL

Gun: TEST BARREL

Barrel length: 7-1/2"

Primer: CCI 400

Case: FA

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
SRA 240	1.705"	No.9	28.0	1753
SRA 240	1.705"	1680	36.0	1702
HDY 250	1.700"	No.9	28.0	1770
HDY 250	1.700"	1680	37.0	1758
SPR 260	1.710"	No.9	26.8	1657
SPR 260	1.710"	1680	35.0	1646
SPR 300	1.765"	No.9	26.0	1596
SPR 300	1.765"	1680	33.5	1591
HDY 300	1.765"	No.9	26.0	1623
HDY 300	1.765"	1680	33.5	1594
FA 240	1.780"	No.9	31.0	1916
FA 240	1.780"	1680	38.0	1769
FA 260	1.765"	No.9	30.0	1835
FA 260	1.765"	1680	38.5	1780
FA 300	1.755"	No.9	25.0	1575

FA 300

1.755"

[1680](#)

34.5

1622

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.



Handgun Loading Data - 50 AE

WARNING: Reduce listed load by 10% for a start charge

50 ACTION EXPRESS

Gun: DESERT EAGLE

Barrel length: 6"

Primer: CCI 350

Case: SPR

Maximum Loads

Bullet	OAL	Powder	Grains	Vel.
325 U-C	1.575"	No.9	23.8	1247
325 U-C	1.575"	1680	37.8	1305

© Copyright 2000 Accurate Arms Company, Inc.

The Accurate logo and all images and text on this web site are the property of Accurate Arms.

Please contact us for reuse.